



ISO HIGH PRESSURE STEEL CYLINDERS FOR INDUSTRIAL GASES

Cylinder Information:


- Semi-finished cylinders manufactured by EKC and distributed by CPI.
- 3/4"-14 NGT internal threads standard, with optional sizes per customer requirement.
- For permanent, liquefiable & embrittling gases
- Manufactured from 34CrMo4 steel
- Cylinders ship with red-oxide primer ready for topcoat.
















| 1 | Cylinder | UNUSA 215/12 | UNUSA 215/14 | UNUSA 215/16 | UNUSA 215/17 | UNUSA 215/19 | UNUSA 215/21 |
|---|----------------------|-----------------|-----------------|-----------------|-----------------|-----------------|-----------------|
| | ISO Spec. | ISO 9809-1 | ISO 9809-1 | ISO 9809-1 | ISO 9809-1 | ISO 9809-1 | ISO 9809-1 |
| 0 | O.D. in/mm | 7.0 | 7.0 | 7.0 | 7.0 | 7.0 | 7.0 |
| | | 178 | 178 | 178 | 178 | 178 | 178 |
| | Wall in/mm | .224 | .224 | .224 | .224 | .224 | .224 |
| | | 5.7 | 5.7 | 5.7 | 5.7 | 5.7 | 5.7 |
| | Length in/mm | 27.2 | 30.9 | 34.6 | 36.6 | 40.4 | 44.1 |
| | | 690 | 785 | 880 | 930 | 1025 | 1120 |
| | Water vol. | 732.3 | 854.3 | 976.4 | 1037.4 | 1160 | 1282 |
| | cu in/liters | 12 | 14 | 16 | 17 | 19 | 21 |
| | Op. Pressure psi/bar | 3118 | 3118 | 3118 | 3118 | 3118 | 3118 |
| | | 215 | 215 | 215 | 215 | 215 | 215 |
| | Weight lbs/kg | 53.1 | 58.8 | 64.6 | 67.7 | 73.4 | 79.4 |
| | | 24.1 | 26.7 | 29.3 | 30.7 | 33.3 | 36 |
| | | | | | | | |

A worldwide supplier of superior products and exceptional customer service, since 1897

